

2" SPG2 AutoGenie™



2" SPG2 AutoGenie™ Skimmer


The 2" SPG2 AutoGenie™ is a safe, reliable and complete system designed to remove free product from 2" or larger wells. The 2" SPG2 AutoGenie system consists of an air-powered pumping unit with a floating inlet that tracks changes in the water level. The SPG float uses specific gravity to avoid water intake, and includes multiple inlet hole positions to allow fine-tuning of the inlet level as the floating layer thickness is reduced. The special Genie bladder pump with high suction capacity delivers proven reliability and durability. The AutoGenie uses an integral pneumatic timer to control the bladder pump fill and discharge times. A complete line of accessories is available, including in-well tubing, well caps, LNAPL collection tank full shutoffs, and other items.

Warranty

SPG2 AutoGenies are warranted for one (1) year.

Advantages

1. Specialized bladder pump is extremely durable, provides high suction to maintain flow, and eliminates contact of drive air with pumped fluid.
2. Continuous, automatic operation that is 100% air powered.
3. Available in a range of flow rates and float travel ranges to best fit site needs.
4. Low air consumption.



The 2" SPG2 AutoGenie™ is available in 6 different models with varying inlet float travel ranges and pumping rates. Why so many options? QED has found that each free product site and well can have its own challenges in terms of well depth, liquid column depth, water level fluctuation and desired LNAPL pumping rate. For example, the model with the longest pump and float travel range may be too long for some wells. Check the dimensions and flow rates below, or just call QED's application specialists to help select the best match for your project.

Specifications

AutoGenie Model	Maximum LNAPL Recovery Rate*	Float Travel Range	Overall Length	Minimum Liquid Column
AG2415 SPG2	160 gpd (605 Lpd)	15 in. (38 cm)	95 in. (241 cm)	6 in. (15 cm)
AG2424 SPG2	160 gpd (605 Lpd)	24 in. (61 cm)	105 in. (267 cm)	12 in. (30 cm)
AG2445 SPG2	160 gpd (605 Lpd)	45 in. (114 cm)	130 in. (330 cm)	15 in. (38 cm)
AG4815 SPG2	320 gpd (1,211 Lpd)	15 in. (38 cm)	118 in. (300 cm)	6 in. (15 cm)
AG4824 SPG2	320 gpd (1,211 Lpd)	24 in. (61 cm)	129 in. (328 cm)	12 in. (30 cm)
AG4845 SPG2	320 gpd (1,211 Lpd)	45 in. (114 cm)	153 in. (389 cm)	15 in. (38 cm)

Minimum Well ID	2 in. (5 cm)
Maximum OD	1.92 in. (4.88 cm)
Maximum Depth	150 ft. (45.7 m)
Air Supply Pressure (min/max)	40/100 psi (2.7/6.9 bar)
LNAPL Fluid Density	< .85 SG
Kinematic Viscosity	1-1000 centistokes
Recommended Initial LNAPL Layer	> 3 in. (> 7.6 cm)
Residual LNAPL Layer	≥ 0.25 in. (.64 cm)
Suitable Types of LNAPL	Gasoline, diesel, jet fuels, kerosene, #2 - #5 fuel oils, light weight motor oil and hydraulic fluid
Materials	Brass, Tygon®, stainless steel, Viton®, Teflon®
Fitting Type	Quick-connect
Hose or Tubing	Both are available

Tygon is a registered trademark of Saint Gobain - Norton. Viton is registered trademark of DuPont Dow Elastomers.

Teflon is a registered trademark of Dupont.

* gpd = gallons per day, Lpd = liters per day