

SLIDER SPECIFICATIONS

Model	SL6000	
Pump Type	Angle-independent positive air displacement	
O.D.	4.5" (11.4 cm)	
Length	69" (175 cm)	
Weight	30 lbs. (13.6 kg)	
Materials	Stainless steel, HDPE, Teflon, Delrin, Viton	
Fittings	Discharge	Stainless steel barb type
	Air Supply	Stainless steel compression
Sizes	Discharge	1 1/4" (32 mm) O.D. tubing
	Air Supply	5/8" (16mm) O.D. tubing
Pump Stroke	1.3 gallons (5 liters) maximum	
Operating Pressure Range	0 - 100 psi (0 - 700 kPa)	
Maximum Lift	200 feet (62 meters)	
Maximum Flow Rate	9.5 GPM/36 LPM (13,680 GPD/51,800 LPD)	
Cap Sizes	4" (150 mm) and up	

ACCESSORIES

MODEL DESCRIPTION

9999*	Well Cap
9999*	Exhaust Valve
37681	5/8" (16 mm) O.D. Nylon Air Supply Tubing
37014	1 1/4" (32mm) O.D. Nylon Discharge Tubing
37060†	Cable - 3/16" (5 mm) Stainless Steel

*Contact QED to determine correct size for your system.

† Note: Slider pump includes Sling Assembly for cable attachment. See Eliminator Accessories on page 17, or consult QED for control equipment.

