

BREAKTHROUGH IN LANDFILL AND REMEDIATION PUMPING

# NEW High Temperature AutoPump® AP4 Ultra




## Reliable, high-performance pump withstands heat – up to 250 °F – with longer runtime between cleanings

The new AutoPump® AP4 High Temperature Ultra (Patent Pending) is field-proven to withstand fluid temperatures as high as 250 °F (121 °C) while delivering superior pumping performance in landfill leachate and condensate risers and groundwater remediation wells. The highly reliable, low-maintenance AP4 Ultra design is enhanced with specialized materials of construction to exceed normal temperature limits.


Proprietary non-stick finishes and electropolished surfaces reduce solids buildup, increasing the interval between required service events. If you need to clean pumps more

than three times a year, you'll save money with Ultra pumps. Parts made of 316 grade Stainless Steel and engineered polymers resist attack by harsh leachates, free-phase and dissolved fuels, BTEX, and MTBE.

Pump cleaning is much faster and easier, often needing only a water spray and a light wipe. Longer run times cut maintenance costs, increase safety of service personnel, and boost project productivity. QED's online Pump Maintenance Cost Comparison Calculator makes it easy to estimate savings and predict the payback period for switching from conventional pumps to a new AP4 Ultra system.



**Longer Runtimes, Easier Service**  
Non-stick finishes resist solids buildup, reduce the frequency of service events, and cut pump cleaning time by half.



**Built to Take the Heat**  
Design for high-temperature use extends pump life and eliminates the need for frequent replacement.



**Complete High Temp System**  
QED has the largest selection of pump tubing and accessories rated for high-temperature applications.



(800) 624-2026 • [www.qedenv.com](http://www.qedenv.com)

P.O. Box 3726 Ann Arbor, MI 48106-3726 USA • (734) 995-2547 • Fax (734) 995-1170 • [info@qedenv.com](mailto:info@qedenv.com)

# NEW High-Temperature AutoPump® AP4 Ultra

## High-Temperature AutoPump® AP4 Ultra

	4" Pump Short AP	4" Pump Long AP	4" Pump Short AP	4" Pump Long AP
Model Number	303276P	303277P	303280P	303281P
Fluid Inlet	Bottom	Bottom	Top	Top
Diameter	3.6 in. (9.1 cm) OD	3.6 in. (9.1 cm) OD	3.6 in. (9.1 cm) OD	3.6 in. (9.1 cm) OD
Length	39.3 in. (100 cm)	51.4 in. (131 cm)	45 in. (110 cm)	61.75 in. (157 cm)
Maximum Flow	13 gpm (49 Lpm)	14 gpm (53 Lpm)	9 gpm (34 Lpm)	10 gpm (38 Lpm)
Maximum Depth	250 ft. (76 m)	250 ft. (76 m)	250 ft. (76 m)	250 ft. (76 m)
Actuation Level	26.7 in. (68 cm)	38.4 in. (98 cm)	41.6 in. (106 cm)	60.3 in. (153 cm)
Pump Volume / Cycle	0.22 - 0.36 gal (.83 - 1.36L)	0.58 - .78 gal (2.2 - 3L)	0.22 - 0.36 gal (.83 - 1.36L)	0.58 - .78 gal (2.2 - 3L)
Air Pressure Range	5 - 120 psi (0.4 - 8.4 kg/cm <sup>2</sup> )	5 - 120 psi (0.4 - 8.4 kg/cm <sup>2</sup> )	5 - 120 psi (0.4 - 8.4 kg/cm <sup>2</sup> )	5 - 120 psi (0.4 - 8.4 kg/cm <sup>2</sup> )
Air Usage	0.4 - 1.1 scf/gal. (3.0 - 8.5 liter of air/fluid liter)	0.4 - 1.1 scf/gal. (3.0 - 8.5 liter of air/fluid liter)	0.35 - 1.1 scf/gal. (3.0 - 8.4 liter of air/fluid liter)	0.35 - 1.1 scf/gal. (3.0 - 8.4 liter of air/fluid liter)
Min. Liquid Density	0.7 SpG (0.7 g/cm <sup>3</sup> )	0.7 SpG (0.7 g/cm <sup>3</sup> )	0.7 SpG (0.7 g/cm <sup>3</sup> )	0.7 SpG (0.7 g/cm <sup>3</sup> )

### Standard Construction Materials

Pump Body	316 Stainless Steel
Pump Ends	316 Stainless Steel
Internal Components	316 Stainless Steel, PVDF, Teflon, Proprietary High Temp. Material
Tube Fittings	316 Stainless Steel
Fitting Type	Barbs, Quick Connects or Easy Fittings

### Tube Options

Tube Material	Red-Line High Temp. Polymer
Sizes - Liquid Discharge	1 in. (25 mm) or 1-1/4 in. (32 mm) OD
Pump Air Supply	1/2 in. (13 mm) OD
Air Exhaust	5/8 in. (16 mm) OD
Tube Material	Nitrile
Sizes - Liquid Discharge	3/4 in. (19 mm) or 1 in. (25 mm) ID
Pump Air Supply	3/8 in. (9.5 mm) ID
Air Exhaust	1/2 in. (13 mm) ID

All models are designed for severe conditions.

With a maximum working temperature of 250° F (121° C) at 100 PSI, Red-Line Tubing will be a problem-solver at your most challenging job sites. High-temperature tubing sets have the same UV protection as QED's high-flow and standard tubing, along with proven chemical resistance to most compounds, so there is no swelling, cracking or breakdown if exposed to sunlight or harsh, corrosive fluids.



**Red-Line™  
High Temperature  
Jacketed Tubing  
Model Number 41140**



- **24/7 Live Support**
- **14 Local Support Offices**
- **East and West Coast Tech Centers**
- **Over 1,000 years of combined experience**
- **On-site installation assistance**
- **OSHA-certified service**
- **Largest inventory of quality pumps, parts, and accessories in the industry; ready for prompt shipment.**



*Innovative Environmental Products*